

KV15-80 KV30-40

High Voltage AC Test Systems



Features

- 0-15kV (KV15-80) or 0-30kV (KV30-40) output voltage
- 1.2kVA output capability
- Key operated supply switch to prevent unauthorised operation
- Dual overload protection
- Variable electronic trip - 10-110% of rated output
- Voltage and current metering
- Zero-volt interlock
- Visual indication of test piece failure

T&R Test Equipment is a market leader in the field of protection test equipment. The range includes primary and secondary current injection equipment up to 6000A, voltage sources, micro-ohmmeters and high voltage test systems up to 100kV.

The KV15-80 and KV30-40 high voltage test sets are general purpose test instruments designed for testing insulation systems and the measurement of breakdown voltage on electrical plant and components.

The units have an output voltage variable from zero to 15kV (KV15-80) or 30kV (KV30-40) with accurate metering on both the output voltage and current. A zero-voltage interlock is provided, ensuring that the output may only be energised with the voltage control at zero.

The output voltage is metered by a large, linear analogue instrument marked 0-20kV on the KV15-80 and 0-40kV on the KV30-40. Both units have a x0.5 range on the voltmeter giving a full scale of 10kV or 20kV respectively. Load current is metered by a second analogue instrument with a full scale of 100mA (KV15-80) or 50mA (KV30-40). A $\div 10$ range is provided on both units, allowing the full scale on the current metering to be reduced by a factor of 10.

The test object and output are protected by an adjustable current trip. The trip level may be set to

10-110% of the rated output in 10% steps. Breakdown of the test object is visibly indicated. The unit must be manually reset after a trip condition before testing can be resumed.

The unit is supplied in a compact, portable case with a permanently connected 2 metre long HV output lead.

The KV30-40 is part of a range of high voltage test systems available from T&R Test Equipment. The ratings of other units available are shown below.

Unit type	Voltage	Current
KV5-100	5kV	100mA
KV15-80	15kV	80mA
KV30-40	30kV	40mA
KV30-100	30kV	100mA
KV50-100	50kV	100mA
KV50-200	50kV	200mA
KV100-100	100kV	100mA



KV100-100



T&R Test Equipment Ltd



KV15-80/KV30-40 Specification

Output

The output of the KV series units is by a permanently connected partially screened high voltage cable.

Unit type	Voltage	Continuous	5 minutes
KV15-80	0-15kV	40mA	80mA
KV30-40	0-30kV	20mA	40mA

The above intermittent on times must be followed by an off time of 15 minutes, and are based on an ambient temperature of 25°C.

If you require a different output voltage test system, please contact us with your specification and we will quote for a custom design.

Metering

The output voltage on both units is metered by a dual range analogue instrument.

Unit	Range	Accuracy
KV15-80	0-10kV	±2% of FS
KV15-80	0-20kV	±2% of FS
KV30-40	0-20kV	±2% of FS
KV30-40	0-40kV	±2% of FS

The output current on the KV15-80 and KV30-40 is metered by a dual range analogue instrument.

Unit	Range	Accuracy
KV15-80	10mA	±2% of FS
KV15-80	100mA	±2% of FS
KV30-40	5mA	±2% of FS
KV30-40	50mA	±2% of FS

Overload Protection

Two overload protection circuits are provided on the KV15-80 and KV30-40. The first is user selectable, and allows trip currents between 10% and 110% of the rated output to be set.

The second trip circuit monitors the primary of the HV transformer, and operates at approximately 130% or rated output current. An overload/trip condition is indicated by an illuminated push button and an audible alarm.

Protection and Safety

The output of the units are protected by variable electronic trips monitoring the output current, and a fixed over-current trip on the primary of the output transformer. The variable trip is adjustable in 10% steps between 10% and 110% of the rated output current.

The input and control supplies are protected by fuses.

The KV15-80 and KV30-40 are designed to meet the requirements of BS EN61010.

An earth terminal is provided on the transformer which must be connected to a low impedance local earth.

Temperature Range

Storage -20°C to 60°C Operating 0°C to 45°C

Dimensions

KV15-80	300x400x470mm	42kg
KV30-40	300x400x470mm	42kg

Weight

Accessories

Supply lead, spare fuse set, operating manual, earth lead, earthing stick.

Note: Due to the company's continuous research programme, the information above may change at any time without prior notification. Please check that you have the most recent data on the product.

EURO-TESTS - Les Bureaux de Sèvres - 2 rue Troyon - 92316 SEVRES - FRANCE

Telephone: +33 (0)141 14 83 31 Fax: +33 (0)141 14 83 01 Email: information@euro-tests.com Web: www.euro-tests.com